

## SL-2M8RP15W40-5MA



### Type of light source:

Lighting technology used:  
LED

Non-directional or directional:  
NDLS

Mains or non-mains:  
NMLS

Connected light source (CLS):  
no

Colour-tuneable light source:  
no

Envelope:  
no

High luminance light source:  
no

Anti-glare shield:  
no

Dimmable:  
yes

### Product parameters:

Energy consumption in on-mode (kWh/1 000 h):  
15

Energy efficiency class:  
F

Useful luminous flux:  
1620 lumen ( Sphere (360°) )

Correlated colour temperature:  
4000K

On-mode power ( $P_{on}$ ) in W:  
15


Standby power ( $P_{sb}$ ) in W:  
0

Networked standby power ( $P_{net}$ ) for CLS in W:  
0


Colour rendering index:  
95

Outer dimensions (length | width | height):  
5000 mm | 8 mm | 3 mm


### Technical drawing



## Energy Label



## Spectral power distribution:



Installation diameter:

-

Installation depth:

-

Connection cable:

mm

IP protection class:

-

Division every mm:

1 mm

External heat sink required:

no

Number of LEDs per metre:

300

Operating temperature:

-

Storage temperature:

-

Net weight:

128 g

EAN Code:

9002843459909

Claim of equivalent power:

no

If yes, equivalent power (W):

-

Chromaticity coordinates (x | y):

0.381 | 0.379

### Parameters for directional light sources:

Peak luminous intensity (cd):

-

Beam angle:

170 °

RoHS 

Must not be disposed of in household waste

**Parameters for LED and OLED light sources:**

*R9 colour rendering index value:*  
72

*Survival factor:*  
1

*lumen maintenance factor:*  
0.96

*L70B50-Lifespan:*  
50000 h

**Parameters for LED and OLED mains light sources:**

*displacement factor (cos  $\phi$ 1):*  
-

*Colour consistency in McAdam ellipses:*  
-

*LED replaces fluorescent light source:*  
no

*If yes then replacement claim (W):*  
-

*Flicker metric (Pst LM):*  
-

*Stroboscopic effect metric (SVM):*  
-

**Safety and installation instructions:**

- >> This product is not a toy and is not suitable for children!
- >> The assembly must be carried out free of voltage!
- >> Do not mount the LED strips / plugs / cables on moving parts, free from tensile and torsional forces. Avoid mechanical stresses such as kinking, bending or chafing!
- >> The SIRO LED system is only suitable for indoor use. Unprotected use outdoors is not permitted. Contact with moisture must be avoided at all costs!

