

# PUSH POWER Datenblatt / Data Sheet



# SL-PP40W2K1

Millable 2-way push button 40 mm (black)





#### **PRODUCT FEATURES**

- ▶ 2-way push button for routing with 35 mm diameter.
- ▶ Battery-free device without external power supply and no wiring necessary!
- Battery-free device without external power supply.
- Transmission energy is generated from mechanical energy when the of the push button.
- Radio-based range up to 80 metres. (open area)
- ▶ Push Button can be connected to any number of Push Power Receivers.
- Functions:

ON - OFF - DIMMING with MONO receiver, (2 areas controllable)

ON - OFF - DIMMING - setting the COLOUR for DUO receivers

- When several switches are used, a changeover switch function is provided.
- Available in white (K60) and black (K1) version.

## **ASSEMBLY**


Can be milled with 35 mm pot hole drill bit

Milling diameter 35 mmMilling depth: min. 14 mm

#### **DIMENSIONS**

Push Taster (DxH): 40 x 17 mm

## TECHNICAL DRAWING



# **TECHNICAL FEATURES**

Transmission protocol: RF 433 mhz

Range (without mesh): 30 metres (indoors)

▶ IP rating: IP20

#### SAFETY AND INSTALLATION INSTRUCTIONS

- This product is not a toy and is not suitable for children!
- lacktriangle The SIRO LED system is only suitable for indoor use.
- ▶ Unprotected outdoor use is not permitted.
- Contact with moisture must be avoided at all costs!

## **SCOPE OF DELIVERY**

- Push button
- Mounting ring