



4-way furniture switch with 60 mm mounting frame (black)

Thank you for choosing a SIRO light switch! This simple guide will help you install and use your new switch.



PRODUCT FEATURES

- ` 4-way switch for controlling SIRO PUSHPOWER Receiver
- ` Compatible with many 55mm switch frame systems.
- ` No battery or wiring required!
- Battery-free device without external power supply.
- `Transmission energy is generated from mechanical energy when actuated the seesaw.
- ` Radio-based range up to 80 meters in open areas.
- 1 button can be connected to any number of Push Power Receivers.
- ` Changeover switch function when using multiple switches.
- Four independent MONO areas or two DUO areas can be controlled.
- ` Available in white (K60) and black (K1) versions
- Frame and base plate included.

MONTAGE

- 1. The surface is clean, free of grease and stable.
- 2. Mill the frame and glue or fix it with screws.
- 3. Plug in the radio module (3).
- 4. Attach the rocker (4).

TECHNICAL FEATURES

- Transmission protocol: RF 433 mhz
- `Range (without mesh): 30 meters (in buildings)
 - IP Rating:


DIMENSIONS


RoHS CE

Must not be disposed of in household waste

Must not be disposed of in household waste

Switch including frame (LxWxH):





60 x 60 x 12 mm

SAFETY AND ASSEMBLY INSTRUCTIONS

IP20

- This product is not a toy and is not suitable for children!
- ` The SIRO LED system is designed for indoor use.
- ` Unprotected outdoor use is not permitted.
- ` Contact with moisture must be avoided at all costs!

SIRO fittings and metal goods factory Spielfeldstrasse 12 4452 Ternberg, Austria Tel . +43 (0)7256.6020.0 Fax . +43 (0)7256.8932 E-Mail office@siro.at Web . www.siro.at © 2024 All rights reserved.

All rights reserved Version 01/24



SPECIAL LIGHTING